

Application No. 10/764,652  
Response to Office Action

Customer No. 01933

Listing of Claims:

1. (Currently amended) A lubricating structure for an outboard motor, comprising:

a vertically installed V-type engine having a side part; and

a main oil gallery formed in said side part of said engine,

5 for allowing lubricating oil to pass therethrough; and

an oil gallery formed substantially in a central part of said engine in a transverse direction of said engine, as a passage separate from said main oil gallery, for allowing oil for cooling pistons to pass therethrough.

2. (Original) A lubricating structure as claimed in claim 1, comprising an oil filter disposed in said side part of said engine at a location close to said main oil gallery in a fashion directly connected thereto, for filtering the lubricating oil.

Claim 3 (Canceled).

4. (Currently Amended) A lubricating structure as claimed in claim 3 1, comprising a coolant passage formed in said engine at a location close to said oil gallery, for cooling said oil gallery.

Application No. 10/764,652  
Response to Office Action

Customer No. 01933

5. (Original) A lubricating structure for an outboard motor, comprising:

a vertically installed V-type engine including a cylinder block having a bottom part and an oil filter;

5 an oil passage formed in said bottom part of said cylinder block; and

a supply passage extending to said oil filter and a return passage extending from said oil filter, said supply passage and said return passage being formed by partitioning said oil  
10 passage.

6. (Original) A lubricating structure as claimed in claim 5, comprising a lid assembly, and

wherein at least one of said supply passage and said return passage has a part thereof formed by casting and covered by said lid assembly to form a passage.

7. (Original) A lubricating structure as claimed in claim 5, comprising a lid assembly, and

wherein one of said supply passage and said return passage has a part thereof formed by casting and covered by said lid  
5 assembly to form a passage, and the other of said supply passage and said return passage is formed in said lid assembly.

Application No. 10/764,652  
Response to Office Action

Customer No. 01933

8. (Original) A lubricating structure as claimed in claim 5, comprising a plurality of distribution passages in communication with said return passage, for distributing oil to component parts of said engine.

9. (Original) A lubricating structure for an outboard motor, comprising:

a cylinder block;

a cylinder head having an oil passage formed therein;

5 a hydraulically driven variable valve timing mechanism;

an oil pump for supplying oil under pressure, the oil supplied under pressure from said oil pump being supplied as driving oil to said variable valve timing mechanism from said cylinder block through said oil passage formed in said cylinder head, and supplied as lubricating oil to said cylinder head; and

10 at least one first passage and at least one second passage formed as passages separate from each other in said cylinder block, for guiding the oil supplied under pressure from said oil pump to said cylinder head;

15 wherein said cylinder block has at least one head-lubricating oil hole formed therein, for supplying the oil supplied through said first passage formed in said cylinder block to component parts within said cylinder head, as lubricating oil; and

Application No. 10/764,652  
Response to Office Action

Customer No. 01933

20            wherein said cylinder block has at least one  
mechanism-driving oil hole formed therein, as a passage separate  
from said head-lubricating oil hole, for supplying the oil  
supplied through said second passage formed in said cylinder  
block to said variable valve timing mechanism, as driving oil.